Summit Treadmill

V-SUM-TR-F

Elevated design and durable performance deliver engaging running experiences in heavy-use fitness facilities.

- Spacious running surface supports natural, confident strides
- Shock-absorbing deck reduces impact for comfort and control
- High-quality drive system offers smooth, long-lasting performance





Product availability may vary by region. Please contact your local office for more information.

Console

Display	56 cm / 22” class capacitive touchscreen LCD
Workouts	Go, manual, Sprint 8, Virtual Active, target heart rate, fat burn, rolling hills, time goal, distance goal, calorie goal, six fitness tests, custom, HIIT mode
Heart Rate	Contact, telemetric, Bluetooth
Languages	English, German, French, Italian, Spanish, Dutch, Portuguese, Chinese-S, Chinese-T, Japanese, Korean, Swedish, Finnish, Russian, Arabic, Turkish, Polish, Welsh, Basque, Vietnamese, Somali, Danish, Thai, Malay, Catalan
Analog TV	Optional: NTSC, PAL, SECAM

Console	
Digital TV	Optional: ATSC 1.0, QAM-B, ISDB-T, ISDB-Tb, DVB-C/S/S2/T/T2
Pro:Idiom Compatibility	Optional (via coax)
WiFi	Yes
USB Port	Yes: USB-A for device charging, device media, software updates
HDMI IN Port	Yes: screen casting from smart devices that support HDMI output
Workout Feedback	Distance, speed, heart rate, watts, METs, pace, calories, time, level, incline
Bluetooth	Yes: heart rate, headphones, FTMS transmits speed and other data to training apps
CSAFE	Yes
NFC	Yes: one-tap connection to Vision Fitness app
QR Code	Yes: connects to console demonstration video and Vision Fitness app download link
Power consumption when turned off	≤ 0.3 W
Power consumption in standby mode	≤ 0.5 W
Frame	
Frame Type	Heavy-gauge welded steel
Running Area	152 x 55.4 cm / 60” x 22”
Cushioning System	UltraZone cushioning system
Running Belt	2-ply waxed belt
Deck Thickness	2.54 cm / 1” reversible
Drive System	4.2 hp AC dynamic response drive system
Speed Range	0.8–22 km/h / 0.5–13.8 mph (220 V) or 0.8–19.3 km/h / 0.5–12 mph (100–120 V)
Incline Range	0–15%
Extras	Water bottle holder, reading rack
Assembled Dimensions (L x W x H)	215 x 91 x 154 cm / 85” x 36” x 61” with DLED, 215 x 91 x 162 cm / 85” x 36” x 64” with ENT
Assembled Weight	173 kg / 382 lbs. with DLED, 179 kg / 395 lbs. with ENT

Frame	
Max User Weight	182 kg / 400 lbs.
Power Requirements	220 V / 50–60 Hz or 100–120 V (may vary by region)
Power Supply	NEMA 6–20 (120 V) or 220 V (may vary by region)