Summit Recumbent Bike

V-SUM-RB-F





Ergonomics, accessibility and commercial-grade engineering combine to deliver reliable, low-impact rides in high-use fitness facilities.

- Footprint 10% smaller than competitors delivers maximum performance in minimal space
- Supportive seating and step-through design maximize comfort and accessibility for all
- Commercial-grade frame and crank assembly deliver stable, confident workouts in demanding environments

Product availability may vary by region. Please contact your local office for more information.

Console	
Display	14 x 10 dot-matrix workout profile LEDs and 22 numeric LEDs
Workouts	Go, manual, fat burn, intervals, constant watts†, goal, target heart rate, fitness tests
	†Some of these programs may not be available on this frame.
Languages	English, German, French, Italian, Spanish, Dutch, Portuguese, Russian, Polish

Console	
WiFi	Optional: for connection to Vision Asset Management
Bluetooth	Yes: connection to Vision Fitness app, heart rate device or FTMS-enabled fitness app
USB Port	Yes: USB-A for device charging and software updates
Workout Feedback	5 displays allow user to toggle between time and distance, resistance level and calories, speed and RPM, watts and METS, heart rate and incline
NFC	Yes: one-tap connection to Vision Fitness app
Tablet Holder	Yes
QR Code	Yes: connects to console demonstration video and Vision Fitness app download link
Power consumption when turned off	≤ 0.3 W
Power consumption in standby mode	≤ 0.5 W
Frame	
Frame Type	Heavy-gauge welded steel
Pedal Type	Self-balancing with adjustable straps
Seat Type	Custom one-piece, molded seat back and bottom
Seat Adjustment	23 positions
Resistance System	Single-stage, self-powered generator
Resistance Range	1–30
Handlebar Design	Console mast and seat-mounted with contact heart rate grips
Extras	Water bottle holder, reading rack
Assembled Dimensions (L x W x H)	149 x 64 x 143.7 cm / 58.6” x 25.2”x 56.5”
Assembled Weight	97.5 kg / 215 lbs.
Max User Weight	182 kg / 400 lbs.
Power Requirements	Self-powered or 100–240 V — 50/60 Hz AC (may vary by region)