Summit Suspension Elliptical

V-SUM-SE-F

Smooth, low-impact motion and a sturdy, commercial-grade frame deliver reliable workouts in demanding fitness environments.

- Footprint 10% smaller than competitors delivers maximum performance in minimal space
- Natural stride design supports smooth, low-impact exercise for users of all kinds
- Heavy-duty commercial frame delivers stable, confident workouts in demanding environments





Product availability may vary by region. Please contact your local office for more information.

Console	
Display	14 x 10 dot-matrix workout profile LEDs and 22 numeric LEDs
Workouts	Go, manual, fat burn, intervals, constant watts†, goal, target heart rate, fitness tests
	†Some of these programs may not be available on this frame.
Languages	English, German, French, Italian, Spanish, Dutch, Portuguese,

Console	
	Russian, Polish
WiFi	Optional: for connection to Vision Asset Management
Bluetooth	Yes: connection to Vision Fitness app, heart rate device or FTMS-enabled fitness app
USB Port	Yes: USB-A for device charging and software updates
Workout Feedback	5 displays allow user to toggle between time and distance, resistance level and calories, speed and RPM, watts and METS, heart rate and incline
NFC	Yes: one-tap connection to Vision Fitness app
Tablet Holder	Yes
QR Code	Yes: connects to console demonstration video and Vision Fitness app download link
Power consumption when turned off	≤ 0.3 W
Power consumption in standby mode	≤ 0.5 W
Frame	
Frame Type	Suspension Elliptical Trainer
Stride Length	51.3 cm / 20”
Step-on Height	24 cm / 9.5”
Power Incline	No
Resistance System	Two-stage, self-powered generator
Resistance Range	1–30
Pedal Type	Oversized with rubber inserts and front guard
Pedal Spacing	5.9 cm / 2.3”
Handlebar Design	Dual action and stationary with heart rate grips
Extras	Water bottle holder, reading rack
Assembled Dimensions (L x W x H)	167 x 77 x 168.5 cm / 65.7” x 30.3” x 66.3”
Assembled Weight	150 kg / 330 lbs.
Max User Weight	182 kg / 400 lbs.
Power Requirements	Self-powered or 100–240 V — 50/60 Hz AC (may vary by region)